

VIABLUE NF-S1 XLR KABEL 3m



Kód:	VBLXLR3M
Výrobce:	VIABLUE
Záruční doba:	24 měsíců



Product description:

ViaBlue? NF-S1 XLR interconnects yield music with faithful reproduction at all frequencies. The sound is completely linear and undistorted. The silver-plating of both screens makes it possible to perceive even the most subtle musical variations in the high-frequency range with high fidelity. The goal is to play back music the same way it was recorded - without any distortion. NF-S1 performs this task exceptionally well.

The balanced construction has two inner tin-plated 0.5 mm² copper wires with 19 individual strands (19 x 0.185 mm) and polyethylene insulation. Two twisted PVC insulators are used as fillers. The Quattro Silver Shield multiple screening has two ALU-PETP films and two silver-plated spiral wrap screens running in opposite directions with fine 0.15 mm strands. There is a felt layer between the screen and the outer cladding to protect the outer silver screen. NF-S1 has an outside diameter of 8 mm.

Terminated with RCA plugs.

NF-S1 XLR cables are assembled with ViaBlue? T6s XLR connectors that have pins made of bronze. They ensure extremely strong contact pressure and thus very low contact resistance. The NF-S1 cables are braided with the ViaBlue? Cobra protective sleeve. NF-S1 interconnects are available as mono and stereo cables. The function is identical. With the mono version you get one pair of two single cables. The stereo version has the two single cables in one sleeving so it's more comfortable to handle when you got many cables.

Technical specifications:

- Outer diameter mono: 2X 9 mm | stereo: 1X 18 mm
- Screenings: 4 (2X spiral screen / 2X foil screen)
- Connectors: T6s xlr connectors
- Finishing: silvered / tinned
- Capacity conductor: 50pF/M | screen: 100 pF/M
- Marking: black / red
- Play in time: appr. 22 hours

Technická data: